

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: **STARQ RECHARGEABLE BATTERY**

Trade Name: **STARQ RETAILS,
3rd Floor, 7A, Plot 69/71,
Jitekar Building, Undira Street,
Chawky Mohalla, Mumbai Central,
Mumbai City, Maharashtra, 400008.**

Phone Number: +91 9769726227

Email: starq.retails@gmail.com

Section 2 - Hazards Identification:

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shred the Li-ion Battery Rechargeable Cell ingredients contained within or their ingredients products could be harmful.
Appearance, Color, and Odor	Solid object with no odor, no color.
Primary Route(s) of Exposure	These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact
Potential Health Effects:	<p>ACUTE (short term): Exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.</p> <p>Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.</p> <p>Ingestion: Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.</p> <p>Skin: Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin.</p> <p>Eye: Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye. CHRONIC (long term): see Section 11 for additional toxicological data</p>
Medical Conditions Aggravated by Exposure	Not applicable



MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Reported as
carcinogen

Not applicable

Section 3 – Composition/Information on Ingredients:

STARQ RECHARGEABLE Battery

Sr. No.	Battery Parameters	
01	Battery Type	Li-Ion
02	Nominal Voltage	62.9v
03	Nominal Capacity	32Ah
04	Battery Watt	2012.8w
05	Cell Configuration	Li-Ion – 3.7v – 32Ah
06	Discharging Current	40Amp (Depend on Discharging Current)
07	Peak Discharging Current	80Amp
08	Max Charging Voltage	71.4v
09	Max Discharging Voltage	46.7v
10	Discharging Temp	-20oC~60o
11	Charging Current	20Amp
12	Charging Temp	-20oC~60oC
13	Weight	Approx. 12 kg
14	Battery Packing	Epoxy sheet with Metal Case

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

15	Dimension (mm)	Length : 175 mm Width : 165 mm Height : 275 mm
16	Passive Protection Function	Over Charge Protection; Over Discharge Protection; Over Current Protection; Cell Balance Function, etc.

TestingCondition:

Standard Charge	Constant current and constant voltage (CC/ CV) Constant Current: 5 Amp Upper limit Voltage: 42V
Standard Discharge	Constant current discharge (CC) Constant current: 7.5 Amp End voltage: 27V

Mechanical Specification:

Dimension	270mm x 90mm x 75mm
Weight	2.75Kg
Casing	Soft pack with open wire

Section 4 – First Aid Measures

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice.
Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.
------------------	--

Section 5 – Fire-fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
----------------------	--

Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases Sensitivity to Static Discharge: Not Applicable
Specific Hazards arising from the chemical	Fires involving Cylindrical Lithium Ion Rechargeable Cell are controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face Self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0

Section 6 – Accidental Release Measures

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7 – Handling and Storage

Handling	The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.
Storage	Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Section 8 – Exposure Controls and Personal Protection

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery. Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

Section 9 - Physical and Chemical Properties

Physical State	Form: Solid
	Color: Black
	Odor: Odorless
Change in condition:	
pH, with indication of the concentration	Not applicable
Melting point/freezing point	Not available.
Boiling Point, initial boiling point and Boiling range:	Not available.
Flash Point	Not available.
Upper/lower flammability or explosive limits	Not available.

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Vapor Pressure:	Not applicable
Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.
Solubility in Water:	Insoluble
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	130°C
Decomposition temperature	Not available.
Odour threshold	Not available.
Evaporation rate	Not available.
Flammability (soil, gas)	Not available.
Viscosity	Not applicable

Section 10 - Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Cylindrical Lithium Ion Rechargeable Cell to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not Available

Section 11 - Toxicological Information

MATERIAL SAFETY DATA SHEET

Revision Date: 27/02/2024

MSDS

Print Date: 27/02/2024 Version: 1.0

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

Section 12 - Ecological Information

General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/Eco toxicity	Not Available
Mobility in soil	Not Available
Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available

Section 13 – Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or

re-used. Observe local, state and federal laws and regulations.

Section 14 – Transport Information

The Cylindrical Lithium Ion Rechargeable Cell (CMICR18650F9M) had passed the UN 38.3 test and is classified as non-dangerous goods and also complies with the UN Recommendations on the Transport of Dangerous Goods; IATA Dangerous Goods regulations, and applicable U.S. DOT regulations for the safe transport of Cylindrical Lithium Ion Rechargeable Cell.

The Cylindrical Lithium Ion Rechargeable Cell is transported according to the PACKING INSTRUCTION 965 Section I B of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES, UN No.: UN3480).

However, the Cylindrical Lithium Ion Rechargeable Cell may also be transported according to the PACKING INSTRUCTION 966 Section II of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES PACKED WITH EQUIPMENT, UN No.: UN3481) or PACKING

INSTRUCTION 967 Section II of IATA DGR 63rd edition (Proper shipping name and UN ID number: LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, UN No.: UN3481).

More information concerning shipping, testing, marking and packaging can be obtained from label master at <http://www.labelmaster.com/>.


Each package must be labeled with a Lithium Battery handling label.

Li-ion batteries treated as “Non-regulated goods” under the United Nations Recommendations on the Transport of Dangerous Goods, Special Provision 188, provided that packaging is strong and prevent the products from short-circuit.

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions (2021-2022 edition).
- The International Air transport Association (IATA) Dangerous Goods Regulations (63rd edition).
- The International Maritime Dangerous Goods (IMDG) Code (Amdt. 40-20).
- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA
- The Office of Hazardous Materials Safety within the US Department of Transportation's (DOT) Research and Special Programs Administration (RSPA)

Section 15 - Regulatory Information

<h1>STARQ RETAILS</h1>	
MATERIAL SAFETY DATA SHEET	Revision Date: 27/02/2024
MSDS	Print Date: 27/02/2024 Version: 1.0

OSHA hazard communication standard (29 CFR 1910.1200)

Hazardous Non-hazardous

Section 16 - Other Information

The information above is believed to be accurate and represents the best information currently available. However, **STARQ RETAILS** makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

Disclaimer:

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. **STARQ RETAILS** shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any terms of this notice.

